



### Section 1. Substance/preparation and company identification

<u>Company</u>	<u>24 Hour Emergency Response Information</u>
Underground Technologies LLC 2546 Elliott Troy, MI 48083	CHEMTREC: (800) 424-9300 UGT Phone: (248) 765-8966 UGTContact: David Wahl

### Section 2. Composition/Information on ingredients

<u>Ingredient Name</u>	<u>CAS Number</u>	<u>Concentration</u>
Amino Silane	1760-24-3	1 — 5%

### Section 3. Hazard identification

#### Overview

Health – 1  
Flammability – 0  
Protective Equipment - 0

**Routes of Entry** — Dermal contact, Eye.

**Acute Eye Contact** — Direct contact can cause severe irritation.

**Acute Skin Contact** — Direct contact may cause slight irritation.

**Skin Absorption** — Not Toxic.

**Acute Inhalation** — Product is extremely low in volatility and therefore not likely to pose a problem from inhalation.

**Acute Ingestion** — May be harmful if ingested, not a likely route of entry.

**Chronic Effects of exposure** — Repeated or prolonged direct contact to the eyes may cause chemical burns. Repeated or prolonged direct contact to the skin may cause a dermatitis.

**Medical Conditions Aggravated by exposure** — Preexisting skin and eye disorders may be aggravated by direct contact to this product.

**Carcinogenicity** — There are no components in this product that are listed as a carcinogen by NTP, IARC, ACGIH or OSHA.

### Section 4. First-aid measures

**First Aid For Eyes** — Flush with large amounts of water for at least 15 minutes. Consult a physician if ill effects or irritation occurs.

**First Aid For Skin** — Clean product from affected area with Ethyl alcohol, then wash with soap and water.

**First Aid for Inhalation** — An unlikely route of entry. Remove to fresh air. Consult a physician.

**First Aid For Ingestion** — An unlikely route of entry. Consult a physician.

### Section 5. Fire-fighting measures

**Special Fire Fighting Instructions** - None.

**Full emergency equipment with self** - contained breathing apparatus and full protective clothing should be worn by firefighters.

**Extinguishing Media** - Water, CO<sub>2</sub>, Dry Chemical, Foam.

**Unusual Fire and Explosion Hazards** - None. This product is not considered flammable.

**Flashpoint** - Not applicable.

**Upper Flammable Limit** - Not applicable.

**Lower Flammable Limit** - Not applicable.



**Autoignition temperature** - Not applicable.  
**Sensitivity to Impact** - Not applicable.  
**Sensitivity to Static Discharge** - Not applicable.  
**Hazardous Combustion Products** - Thermal decomposition may produce toxic fumes of Carbon Monoxide and/or Carbon dioxide.

#### Section 6. Accidental release measures

**Personal Precautions** - Use personal protection recommended in section 8.  
**Methods For Cleaning Up** - Collect spill with absorbent material such as cardboard and place into a container Approved for waste disposal.

#### Section 7. Handling and storage

**Handling** - Use personal protection recommended in section 8. Avoid eye, skin and clothing contact.  
**Storage** - Store in a cool dry area (this product polymerizes when in contact with moisture.)

#### Section 8. Exposure controls and personal protection

**Exposure Guidelines** - No established limits.  
**Engineering controls** - No specific controls are needed.  
Personal Protective Equipment:  
**Eye Protection** - Wear safety glasses or goggles to avoid eye contact.  
**Skin Protection** - Wear impervious gloves such as vinyl to minimize contact with skin.  
**Respiratory Protection** - Not required.  
**Work/Hygienic Practices** - Avoid contact with eyes and skin. Wash thoroughly after handling and before eating or drinking.

#### Section 9. Physical and chemical properties

**Physical State** - Paste.(reacts with moisture to become a firm synthetic rubber)  
Odor and appearance Mild ester odor, thick paste of various colors.  
**pH** - Not established.  
**Specific Gravity** - Varies from color to color. All colors are heavier than water.  
**Density** - 13.35 lbs/gal.  
**Vapor Density** (air = 1) > 1  
**Vapor Pressure (mmHg)** -Not established.  
**Evaporation Rate** - Not Applicable  
  
**Boiling Point** - Not established.  
**Freezing Point** - Not established.  
**Coefficient of Water/Oil Distribution** Not established  
**Viscosity**..... — 800,000 cP

#### Section 10. Stability and reactivity

**Stability** — Considered Stable.  
**Conditions to Avoid** — None known  
**Incompatible Materials** — None known.  
**Hazardous Decomposition Products** — None known. Hazardous polymerization — Will not occur.  
**Reactivity** — Hazardous reaction will not occur.



#### Section 11. Toxicological information

Information below is based on Amino Silane (refer to sections 2.and 3.)

**Oral — Result:** LD50 > 2,000 mg/kg. Remark: Very low order of toxicity.

**Skin Absorption — Result:** LD50 > 2,000 mg/kg. Remark: Very low order of toxicity.

**Skin Direct contact — Result:** Slight irritation.

**Eye Direct contact — Result:** Severe irritation. Remark: Causes corneal injury.

**Inhalation — Result:** LC50 Not cutely Toxic.

**Exposure Limits —** Not applicable.

**Sensitization —** No.

**Reproductive Toxicity —** No.

**Mutagenicity —** No.

**Teratogenicity —** No

**Synergistic Products —** None.

#### Section 12. Ecological information

No known applicable information.

#### Section 13. Disposal considerations

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. This product becomes a firm synthetic rubber when cured. Please allow to cure before disposal.

#### Section 14. Transport information

Special Shipping Information — None.

**DOT —** Not regulated.

**TDG —** Not available.

**PIN —** Not available.

#### Section 15. Regulatory information

OSHA 29 CFR 1910-1200 — Irritant.

TSCA — All components of this product are listed on TSCA Inventory.

CERCLA Reportable Quantity — Not applicable.

SARA Title III:

Section 302 Extremely Hazardous Substances — None.

Section 304 — Not applicable.

Section 311/312 — Immediate (acute) health hazard.

Section 313 —

None. RCRA — Refer

to section 13.

California Proposition 65 — This product contains no levels of listed substances which the state of

California has found to cause cancer, birth defects or other reproductive harm.

WHIMS Classification — D2B



Material Safety Data Sheet  
Product: SECURE N SEAL  
Mfg: Underground Technologies LLC

---

**Section 16. Other information**

Prepared in accordance with 29 CFR 1910.1200

This Product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.



Material Safety Data Sheet  
Product: SECURE N SEAL  
Mfg: Underground Technologies LLC

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITH INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY UNDERGROUND TECHNOLOGIES HERE UNDER ARE GIVEN GRATIS AND VISURON TECHNOLOGIES ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION DESIGNS, DATA AND" INFORMATION GIVEN OR RESULTS OBTAINED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

---

END OF MSDS